

Lackierte Stahlrohrstützen



Lackierte Stahlrohrstützen

Eigenschaften

- Innenrohr Ø 48,3 mm, Außenrohr Ø 57 mm
- Tauchbadlackierung
- Farbe: enzianblau
- Handquetschsicherung
- optimiert nach DIN EN 1065 Klasse B



Auszugs- länge (m)	B 250	B 300	B 350	B 400
	1,58- 2,50 m ca. 14 kg	1,78- 3,00 m ca. 15 kg	2,05- 3,50 m ca. 16 kg	2,30- 4,00 m ca. 18 kg
1,5	30,0			
1,6	30,0			
1,7	30,0			
1,8	30,0	30,0		
1,9	27,7	30,0		
2,0	25,0	30,0	30,0	
2,1	22,6	27,2	30,0	
2,2	20,6	24,7	28,9	
2,3	18,9	22,6	26,4	30,0
2,4	17,3	20,8	24,3	27,7
2,5	16,0	19,2	22,4	25,6
2,6		17,7	20,7	23,6
2,7		16,4	19,2	21,9
2,8		15,3	17,8	20,4
2,9		14,2	16,6	19,0
3,0		13,3	15,5	17,7
3,1			14,5	16,6
3,2			13,6	15,6
3,3			12,8	14,6
3,4			12,1	13,8
3,5			11,4	13,0
3,6				12,3
3,7				11,6
3,8				11,0
3,9				10,5
4,0				10,0



Elvermann GmbH

Zur Reithalle 72-76
D-46286 Dorsten

Fon +49(0)2369/9891-0
Fax +49(0)2369/9891-95

Niederlassung Kleyer Weg 37
D-44149 Dortmund-Kley

Fon +49(0)231/618049-90
Fax +49(0)231/618049-91

Internet:
www.elvermann.de
E-Mail:
info@elvermann.de

ELVERMANN
Schaltechnik